

Professional film made from 80-micron thick PVC polymer, coated with acrylic pressure-sensitive adhesive.

Outdoor durability 8 years



**Technical specifications :**

Thickness: 80 microns

Storage: -5°C to +40°C

Matt white frosted appearance

Thermoformable: No

Protective liner:  
140 g/m<sup>2</sup> siliconized PE paper

Durability: over 8 years outdoors

Temperature resistance: -40°C to +90°C

- Outdoor use ✓
- Extreme climatic conditions ✓
- Light-permeable film ✓
- Permanent bonding ✓
- Easy to install ✓
- Water-based bonding ✓
- Dry bonding ✓

**Application:**

Support:  
Glazing application

Application temperature: between 10 and 30°C



**Advice from mpa pro :**

We recommend water-bonding.

Recommended installation temperature: +20°C

**Limite of use :**

- Wavy or highly irregular surfaces
- Substrates that do not have a clean, smooth surface
- Materials with low cohesion between paint and substrate
- Stainless steel
- Flexible substrates
- 3-dimensional surfaces (e.g. balls, pyramids)

**Will not stick to the following materials:**

- Leather ✗
- Unvarnished wood ✗
- Textile ✗

**Maintenance tip :**

Soapy water solution

Installation video: **Please note that the video shows the grey frosted film.**

